

VOROB'YEVA, L. A.

VOROB'YEVA, L. A. --"Solonetz Soils of the Western Caspian Region." Soil
Biology Faculty. Moscow, 1956. (Dissertation for the Degree of
Candidate in Biological Sciences.)

So.: Knizhnaya Litopis', No 7, 1956.

KAMAY, Gili'm; CHERNOKAL'SKIY, B.D.; VOROB'YEVA, L.A.

Interaction of trialkylarsine oxides with alkyl halides. Dokl. AN
SSSR 145 no.2:323-329 JI '62. (MIRA 15:7)

1. Kazanskiy khimiko-tekhnologicheskii institut imeni Eirova.
Predstavleno akademikom A.Ye.Arbutovym.
(Arsine oxide) (Alkyl halides)

SHCHEGOLEV, N.N.; VOROB'YEVA, L.D.

Experiment in the reorganization of shops for fancy men's footwear.
Kozh.-obuv.prom. 3 no.2;26-28 F '61. (MIPA 14:4)
(Shoe manufacture) (Assembly-line methods)

VOROB'YEVA, L.D., insh.; SHCHEGOLEV, N.N., insh.

Organizing cyclic feeding of lasts. Kosh.-obuv.prom. no.9:
32-34 8 '59. (MIRA 13:2)
(Shoe manufacture) (Assembly-line methods)

VOROB'YEVA, L.I., ~~XXXXXXXXXXXXXXXXXXXX~~ Cand Bio Sci--(diss) "Fermentation of various sources of carbon with propionic acid bacteria." Mos, 1958.
19 pp with diagrams (Acad Sci USSR. Inst of Microbiology), 130 copies
(KL, 45-58, 144)

- 48 -

ABEYDULINA, V.A.; ANNENKOV, G.V.; YEPKHIYEVA, L.G.; VOROB'YEVA,
L.I., red.

[Methodology for determining the level of production mechanization in confectionery enterprises] Metodika opredelenia urovnia mekhanizatsii proizvodstva na predpriatiakh konditerskoi promyshlennosti. Moskva, Izd-vo "Pishchevaia promyshlennost'," 1964. 99 p. (MIRA 17:4)

1. Moscow. Vsesoyuznyy nauchno-issledovatel'skiy institut konditerskoy promyshlennosti. 2. Tsentral'nyy nauchno-issledovatel'skiy institut konditerskoy promyshlennosti, otdel ekonomiki (for Abeydulina, Annenkov, Yepkhiyeva).

VOROB'YEVA, L.I.

Carbon balance during the fermentation of lactic and pyruvic acids
by Propionibacterium. [with summary in English] Mikrobiologiya
27 no.3:287-293 My-Je '58 (MIRA 11:9)

1. Institut mikrobiologii AN SSSR.

(PROPIONIBACTERIUM, metabolism

lactic & pyruvic acid fermentation, eff. on carbon
balance (Rus))

(LACTIC ACID,

fermentation by Propionibacterium, eff. on carbon
balance (Rus))

(PYRUVATES,

same (Rus))

VOROB'YEVA, L.I.

Effect of some trace elements on vitamin B₁₂ production by propionic acid bacteria. Dokl.AN SSSR 138 no.2:450-453 My '61. (MIRA 14:5)

1. Institut mikrobiologii nauk SSSR. Predstavleno akademikom V.N. Shaposhnikovym.
(Cyanocobalamine) (Trace elements) (Propionibacterium)

KURKO, V.I., red.; VOROB'YEVA, L.I., red.; SOKOLOVA, I.A., tekhn.red.

[Smoking of meat products; popular presentation of the scientific principles of smoking] Kopchenie izdelii iz miasa; populiarnoe izlozhenie nauchnykh osnov kopchenia. Moskva, Pishchepromizdat, 1963. 86 p.

(MIRA 17:3)

SOV/20-121-2-45/53

AUTHOR: Vorob'yeva, L. I.

TITLE: The Conditions for the Glycerin Fermentation by Propionibacteria (Usloviya sbrzhivaniya glitserina propionovokislymi bakteriyami)

PERIODICAL: Doklady Akademii nauk SSSR, 1958, Vol. 121, Nr 2, pp. 362-365 (USSR)

ABSTRACT: The author found that the bacteria mentioned cannot ferment glycerin in contrast to lactic and pyruvic acids. The high degree of the reduction (vosstanovlennost') of the glycerin molecule on the one hand and the lack of the corresponding hydrogen acceptors on the other hand apparently did not create any favorably conditions for the constructive exchange in the bacterial nutrient on a synthetic medium. The Propionibacterium Jensenii of Swiss cheese was used for the experiments. A simple medium was produced: $(\text{NH}_4)_2\text{SO}_4$ 0,3%, K_2HPO_4 0,2%, glycerin 1%; vitamins: pantothenic acid 100 - 1 000 μ /l, biotin 0,2 - 1 μ /l, thiamin 10 - 50 μ /l. According to Kvestell three conditions are required for the development of bacteria:

- 1) The organism must be capable of activating the present or-

Card 1/4

SOV/20-121-2-45/53

The Conditions for the Glycerin Fermentation by Propionibacteriae

ganic compound - the hydrogen acceptor. 2) In the transformation of the organic matter energy must be freed which is used by the bacteria for purposes of synthesis; 3) The organic matter itself or its decomposition products must be suited for the formation of the bacterial cell (according to Ref 1). In view of the properties of the glycerin molecule the synthetic medium selected did not meet with any of the three demands mentioned, and no development took place in it. Only when fumaric acid was added as hydrogen acceptor (0,1%) the glycerin fermentation set in (Table 1). From this may be seen that without fumaric acid no formation of bacteria takes place. On fumaric acid alone they cannot form either. The participation of fumaric acid in the constructive metabolism is possible which fact was substantiated by the determination of the biomass (Table 2). The presence of fumaric acid triples the biomass and lengthens the bacterial cells. Fumaric acid possibly substituted the lacking carboxylic acid. Only in higher inoculation rates (6 instead of 3%) the oxygen stimulated the development (Table 3). In the case of a 3% inoculation the glycerin fermentation could be achieved by the addition of 0,07 - 0,1% of yeast autolyzate (Table 4). The addition of

Card 2/4

SOV/20-121-2-45/53

The Conditions for the Glycerin Fermentation by Propionibacteriae

asparagic acid (0,2%) promoted the formation of bacteria only on aerobic conditions (Table 5). Finally the dynamics of the development of the bacteria with 0,2% asparagic acid and a 6% inoculation was investigated on relatively anaerobic conditions (Table 6). Besides propionic acid also acetic acid is formed in the fermentation. The work was carried out under the supervision of V. N. Shaposhnikov, Member, Academy of Sciences, USSR. There are 1 figure, 6 tables, and 3 references, 1 of which is Soviet.

ASSOCIATION: Institut mikrobiologii Akademii nauk SSSR (Institute of Microbiology, AS USSR)

PRESENTED: March 20, 1958, by V. N. Shaposhnikov, Member, Academy of Sciences, USSR

SUBMITTED: March 15, 1958

Card 3/4

SOV/20-121-2-45/53

The Conditions for the Glycerin Fermentation by Propionibacteriae

Card 4/4

VOROB'YEVA, L.I.

Effect of some trace elements on the development and formation of
vitamin B₁₂ by propionibacteria; toxic effect of Zn ions. Dokl.
AN SSSR 145 no.6:1381-1384 Ag '62. (MIRA 15:8)

1. Predstavleno akademikom V.N.Shaposhnikovym.
(Cyanocobalamin) (Zinc--Toxicology) (Propionibacterium)

VOROB'YEVA, L.I.

Effect of sodium hyposulfite on the biosynthesis of vitamin B₁₂
by Propionibact. Jensenii. Dokl. AN SSSR 146 no.3:693-695 S 162.
(MIRA 15:10)

1. Institut mikrobiologii AN SSSR. Predstavleno akademikom V.N.Shaposhnikovym.
(SODIUM THIOSULPHATE) (CYANOCOBALAMIN) (PROPIONIBACTERIUM)

SHAPOSHNIKOV, V.N.; VOROB'YEVA, I.I.

Development of propionibacterium and the synthesis of vitamin B₁₂
on synthetic and natural media. Mikrobiologiya 32 no.2:204-208¹²
Mr-Apr '63. (MIRA 17:9)

1. Institut mikrobiologii AN SSSR.

VOROB'YEVA, L.I.; KUZNETSOVA, V.S.

Effect of $MnSO_4$ on the formation of vitamin B-12 by propionic
acid bacteria. Mikrobiologiya 33 no.1:26-30 Ja-F '64.
(MLRA 17:9)

1. Institut mikrobiologii AN SSSR.

KRAMLI, A.; VOROB'YEVA, L.I.

Effect of oxidation-reduction conditions on the formation of vitamin B₁₂ by propionic acid bacteria. Mikrobiologiya 33 no.3:408-414 (MIRA 18:12) My-Jo '64.

1. Biologo-pochvennyy fakul'tet Moskovskogo gosudarstvennogo universiteta. Submitted March 26, 1963.

VOROB'YEVA, L.I.

Separation of cobalaminins by the thin-layer chromatography
method. Mikrobiologiya 34 no.1:180-183 Ja-F '65. (MIRA 18:7)

1. Biologo-pochvennyy fakul'tet Moskovskogo gosudarstvennogo
universiteta imeni M.V. Lomonosova.

USSR/Physiology of Plants - Photosynthesis.

I-1

UOROB'YEVA L.M.

Abs Jour : Ref Zhur - Biol., No 3, 1958, 10353

Author : Krasnovskiy, A.A., Vorob'yeva, L.M., Pakshins, Ye.V.

Inst : Institute of Biochemistry, Academy of Sciences USSR

Title : Investigation of the Photochemically Active Form of Chlorophyll in Plants of Various Systematic Groups.

Orig Pub : Fiziol. rasteniy, 1957, 4, No 2, 124-133

Abstract : Using as subjects of research plants of various systematic groups the absorption spectra in the red area of the spectrum and the kinetics of chlorophyll bleaching were investigated over the whole of the vegetation period. A detailed method of acquiring "green solutions" is given, as are measurements of the kinetics of bleaching and of the absorption spectra. Chlorophyll bleaching after irradiation with intense red light varied within the limits of 1-30%,

Card 1/2

USSR/Physiology of Plants - Photosynthesis.

I-1

Abs Jour : Ref Zhur - Biol., No 3, 1958, 10353

depending upon the plant; it was not correlated with their position in the system /sistematicheskoye polozheniye/. Beet, orache (Atriplex), marchantia, poplar, fern, and willow possessed the greatest bleaching intensity, while in most plants bleaching varied between 5% and 7%. In plants with the highest bleaching percent the absorption maximum was displaced several m into the short-wave part, thus confirming the presence of a large quantity of the monomeric (active) form of chlorophyll in their chloroplasts. When the monomeric form is separated by centrifugation from the more heavily aggregated form, the absorption maximum is displaced 2-6 m into the short-wave part. The bleaching process was invariably accompanied by displacement of the maximum into the long-wave part. In June and July there was 20-30% bleaching in the sugar beet, while it was only 3-6% in September and October. The project was completed in the Institute of Biochemistry, Academy of Sciences USSR.

Card 2/2

VOROB'YEVA, L.M., KRASNOVSKIY, A.A.

Reversible photoreduction of chlorophyll and sensitized reactions
in homogenates of sugar beet leaves [with summary in English]
Biokhimiia 23 no.5:760-771 S-O '58 (MIRA 11:11)

1. Institut biokhimiia imeni A.N. Bakha AN SSSR, Moskva.
(PLANTS, EFFECT OF LIGHT ON)
(CHLOROPHYLL)
(PLANTS, EFFECT OF ASCORBIC ACID ON)

BELAVTSEVA, Ye.M.; VOROB'YEVA, L.M.; KRASNOVSKIY, A.A.

Study of the structure of aggregated chlorophyll. Biofizika 4
no.5:521-532 '59. (MIRA 14:6)

1. Institut biokhimii imeni A.N.Bakha AN SSSR, Moskva i Laboratoriya
elektronnoy mikroskopii AN SSSR, Moskva.
(CHLOROPHYLL)

VOROB'YEVA, L.N., zootekhnik

Characteristics of the development of new lines of Urzhum boars.
Zhivotnovodstvo 22 no.2:43-48 F '60. (MIRA 15:11)
(Kirov Province--Boars)

VOROBYEVA, L. M., DROZDOVA, N. N., YEROKHIN, YU. YE., KRASNOVSKY, A. A.,
PAKSHINA, YE. V., UMRIKHINA, A. V., BRIN, G. P. (USSR)

"Different Forms of Chlorophyll and its Analogues and their
Role in Processes of Photochemical Electron (or Hydrogen)
Transfer."

Report presented at the 5th International Biochemistry Congress,
Moscow, 10-16 August 1961

DOMAN, N.G.; KRASNOVSKIY, A.A.; ROMANOVA, A.K.; VOROB'YEVA, L.M.; PAKSHINA, Ye.
V.; TERENT'YEVA, Z.A.

Chlorophyll synthesis and carbon dioxide fixation in etiolated barley
seedlings during exposure to light. Fiziol. rast. 8 no.1:3-12 '61.
(MIRA 14:3)

I. A.N. Bakh Institute of Biochemistry, U.S.S.R. Academy of Sciences,
Moscow.

(Chlorophyll) (Photosynthesis)

VOROB'YEVA, L.M.; BYSTROVA, M.I.; KRASNOVSKIY, A.A.

Phytolic and nonphytolic forms of pigments in leaves and homogenates.
Biokhimiia 28 no.3:524-534 My-Je '63. (MIRA 17:2)

1. Institute of Biochemistry, Academy of Sciences of the U.S.S.R.,
Moscow.

LETOKHOV, V.S.; VATSURA, V.V.; PUKHLIK, Yu.A.; FEDOTOV, D.I.; KOSOZHNIKIN,
A.S.; ZHABOTINSKIY, M.Ye.; DASHEVSKAYA, Ye.I.; KOZLOV, A.N.;
RUVINSKIY, L.G.; VASIN, V.A.; YURGENEV, L.S.; NOVOMIROVA, I.Z.;
PETROVA, G.N.; SHCHEDROVITSKIY, S.S.; BELYAYEVA, A.A.; BRYKINA,
L.I.; GLEBOV, V.M.; DRONOV, M.I.; KONOVALOV, M.D.; TARAPIN, V.N.;
MIKHAYLOVSKIY, S.S.; ZHEGALIN, V.G.; ZHABIN, A.I.; GRIBOV, V.S.;
MAL'KOV, A.P.; CHERNOV, V.N.; RATNOVSKIY, V.Ya.; VOROB'YEVA, L.M.;
MILOVANOV, M.M.; ZARIPOV, M.F.; KULIKOVSKIY, L.F.; GONCHARSKIY,
L.A.; TYAN KHAK SU

Inventions.. Avtom. i prib. no.1:78-80 Ja-Mr '65. (MIRA 18:8)

RAKHSHTADT, A.G., kand.tekhn.nauk; ROOEL'BERG, I.L., kand.tekhn.nauk;
VOROB'YEVA, L.P., inzh.; PUCHKOV, B.I., inzh.

Effect of heat treatment on the properties and structure of
beryllium bronze. Metalloved.i term.obr.met. no.2:20-31 P '60.

1. Moskovskoye vyssheye tekhnicheskoye uchilishche imeni Baumana
i Giprotsvetmetobrabotka.
(Bronze--Heat treatment)
(Copper-Beryllium alloys--Metallography)

18.1215,18.7100

77592
SOV/129-60-2-5/13

AUTHORS: Rakhshtadt, A. G., Rogel'berg, I. L. (Candidates of Technical Sciences), Vorob'yeva, L. P., Puchkov, B. I. (Engineers)

TITLE: Effect of Heat Treatment on Properties and Structure of Beryllium Bronze

PERIODICAL: Metallovedeniye i termicheskaya obrabotka metallov, 1960, Nr 2, pp 20-31 (USSR)

ABSTRACT: Beryllium bronze possesses elastic properties, high corrosion resistance, and adequate electric conductivity. It is used for the elastic elements of instruments and devices. Inasmuch as previous works failed to study the elastic properties of this bronze, the authors investigated elastic and relaxation properties of the bronze prepared in the form of thin strip. The modulus of elasticity was determined by the dynamic method according to the frequency of resonant-type vibration of a cantilever

Card 1/10

Effect of Heat Treatment on Properties
and Structure of Beryllium Bronze

77592
SOV/129-60-2-5/13

specimen. Elastic limit was determined by means of longitudinal bending of the specimen according to the method described in Rakhshtadt, A. G., and Shtremel', M. A., Collection MVTU imeni Bauman, Physical Metallurgy and Heat Treatment, Mashgiz, 1955. Residual elongation of the external fiber was calculated by formulas of Ye. P. Popov (Popov, Ye. P., Theory and Calculation of Flexible Elastic Parts, Publishing House LKVVIA, 1947). Permissible residual deformation in determining elastic limit amounted to 0.001 to 0.01%. Relaxation characteristic was determined on the strip bend around mandrels of various diameters. The following types of bronze were investigated: (1) Br B2 (Be, 2.07; Ni, 0.2%); (2) Br B2.5 (Be, 2.56; Ni, 0.31%); (3) Br BNT (Be, 1.9 to 2.02; Ni, 0.32; T, 0.19%). For this purpose, 10-kg ingots 40 mm thick were hot-rolled at 600-800° C into 4.5 mm thick strip with maximal reduction of 20-30%

Card 2/10

Effect of Heat Treatment on Properties
and Structure of Beryllium Bronze

77592

SOV/129-60-2-5/13

per pass. Rolled strip was hardened from 800° C (holding time 1 hr and water quenching). After pickling, specimens were cold-rolled and hardened according to the above rates at strip thicknesses of 3, 1.5, and 0.7 mm. Then, the strip was rolled to 0.6, 0.43, 0.33, and 0.30 mm thickness. Subsequently, the specimens were hardened in water from 780 to 790° C and rolled to an identical thickness of 0.3 mm; i.e., with reductions of 50, 30, and 10% and without deformation. Hardening from 780 to 790° C (holding for 10 min and water-cooling at 20° C) was done, since such heating brings about a sufficient concentration of beryllium in alpha-solution and fine grain structure (10-15 μ grains). Mechanical and physical properties of the above bronze specimens corresponded to those given in literature for bronzes containing 2 and 2.5% Be. Figure 2 shows changes of elastic properties, hardness, and electrical resistance of bronze Br B2.5 under the effect of tempering. Similar figures are given in the paper for the other two types of bronze.

Card 3/ 10

Effect of Heat Treatment on Properties
and Structure of Beryllium Bronze

77592

SOV/129-60-2-5/13




Fig. 2.

See Card 5/10 for caption.

Card 4/10

Effect of Heat Treatment on Properties
and Structure of Beryllium Bronze

77592

SOV/129-60-2-5/13

Caption to Fig. 2 on Card 4/10

Fig. 2. Change of elastic properties, hardness, and electrical resistance of beryllium bronze Br B2.5 after tempering. (a) — at 320° C; ----- at 350° C; (b) at 370° C. σ_{el} , elastic limit;

E, modulus of elasticity; ρ , electrical resistance, $\frac{\text{ohm} \cdot \text{mm}^2}{\text{m}}$; H_v , Vickers hardness; subscripts at

$\sigma_{0.005}$, $\sigma_{0.002}$, $\sigma_{0.01}$, residual deformation.

Bronze Br BNT 1.9 has a higher elastic limit than the other two types of bronze. It also exceeds that indicated in Richards, J., Materials and Methods, Vol 31, Nr 4, 1950, and in some Soviet references. This may be ascribed not only to a different method of investiga-

Card 5/10

Effect of Heat Treatment on Properties
and Structure of Beryllium Bronze

77592

SOV/129-60-2-5/13

tion but also to the use of thin strip with a highly homogeneous structure. The rate of relaxation at the initial stress equal to elastic limit (at $\sigma_{0.005}$) is higher after tempering at 320° C for 3 hours than that after tempering at 350° C for 1 hour or at 370° C for 20 minutes (see Fig. 7).

Card 6/10

Effect of Heat Treatment on Properties
and Structure of Beryllium Bronze

77592

SOV/129-60-2-5/13




Fig. 7. Change of stresses as the result of relaxation of beryllium bronze at 20° C after hardening and tempering. (a) 320° C, 3 hr; (b) 350° C, 1 hr; (c) 370° C, 20 min; (d) 350° C after reduction of 30%.

Card 7/10

Effect of Heat Treatment on Properties
and Structure of Beryllium Bronze

77592

SOV/129-60-2-5/13

Plastic deformation following hardening strengthens the bronze and increases its elastic limit and hardness, but affects the modulus of elasticity only slightly (see Fig. 9).




Fig. 9. Change of elastic properties, hardness, and electrical resistance of beryllium bronze Br 2.5 after hardening, cold plastic deformation (reduction 30%), and tempering: — at 300°C ; ---- at 350°C .

Card 8/10

Effect of Heat Treatment on Properties
and Structure of Beryllium Bronze

77592

SOV/129-60-2-5/13

As a result of this study the following conclusions have been made: (1) heat treatment and plastic deformation drastically affect elastic properties and structure of beryllium bronze; (2) tempering at 350-370° C increases elastic limit and modulus of elasticity of hardened bronze which reaches its maximum with a holding time of 1 hour at 350° C and 20 minutes at 370° C; (3) bronzes containing 2 or 2.5% Be behave identically in regard to strengthening. Additions of Ti bring about a further increase of the elastic limit; (4) bronzes with 2.5 and, particularly, with 2% Be are characterized by nonuniform microscopic decomposition in tempering with higher rates of decomposition along grain boundaries; (5) deformation of hardened bronze changes the state of initially hardened solid solution only with high reduction (30 and 50%); (6) tempering of hardened beryllium bronze subjected to plastic deformation promotes the value of elastic limit ($\sigma_{0.001}$ =

Card 9/10

Effect of Heat Treatment on Properties
and Structure of Beryllium Bronze

77592

SOV/129-60-2-5/13

100 kg/mm²). There are 10 figures; 4 tables; and 38 references, 22 Soviet, 12 U.S., 2 German, 1 U.K., 1 French. The 5 most recent U.S. and U.K. references are: Kelly, A., Acta Metallurgica, Nr 8, 1958; Richards, J., ASTM, Spec. Tech. Publication, Nr 129, 1952; Richards, J., Materials and Methods, Vol 31, Nr 4, 1950; Beck, P., Journ. Appl. Physics, Vol 20, Nr 7, 1949; Friedel, J., Phil. Magazine, Vol 44, Nr 351, 1953.

ASSOCIATION: Moscow Higher Technical School imeni Bauman (MVTU imeni Baumana), State Design and Planning Scientific Research Institute for Working of Nonferrous Metals (Giprotsvetmetobrabotka)

Card 10/10

L 38558-66 EWT(m)/EWP(w)/EWP(v)/T/EWP(t)/ETI/EWP(R)/IJP(c), JD/HM/GD

ACC NR: AT6012405

SOURCE CODE: UR/0000/65/000/000/0295/0300

AUTHORS: Guseva, Ye. A.; Komarov, M. A.; Vorob'yeva, L. P.; Savitskiy, I. A.

ORG: none

TITLE: Structural and property changes of the basic metal and welded joints of alloy VT15 during heat treatment

SOURCE: Soveshchaniye po metallokhimii, metallovedeniyu i primoeniyu titana i yego splavov, 6th. Novyye issledovaniya titanovykh splavov (New research on titanium alloys); trudy soveshchaniya. Moscow, Izd-vo Nauka, 1965, 295-300

TOPIC TAGS: METAL AGING, MECHANICAL PROPERTY, titanium alloy, metal welding, metal property, weld heat treatment: / VT15 titanium alloy

ABSTRACT: The aging process of the basic metal and welded joints of alloy VT15 was experimentally investigated on specimens which (after quenching in water from 800C) had the following properties: $\sigma_2 = 101.5 \text{ kg/mm}^2$, $\sigma_{0.2} = 100.7$; $\delta = 11.7\%$, $\alpha = 6.2 \text{ kg/cm}^2$, bending angle = 75° . The structural, mechanical, and electrical resistance changes after heat treatment were investigated. Quenching temperatures were varied from 650--1100C (quenching in water after 15 min at temperature) and aging temperatures from 300--600C. Curves of resistivity and α as a function of quenching and aging temperature are presented along with sample photographs of the corresponding microstructures, and the results are summarized in two tables. It was

Card 1/2

L 38558-66

ACC NR: AT6012405

3
found that quenching temperature had little effect on the mechanical properties and microstructure of the base alloy but did affect the metal resistivity (maximum for 800-900C). All the welded joint properties were affected by both the quenching and aging temperatures. It was concluded that the kinetics of structural and phase transformations during heat treatment is different for the base alloy and the welded joints and thus requires detailed study. M. V. Polyanski performed the electron-microscopic studies of the joints. Orig. art. has: 2 tables and 5 figures.

SUB CODE: 11, 13/ SUBM DATE: 02Dec65/ ORIG REF: 003

Card 2/2 MLP

OZIMOV, B.V., dotsent, kand.tekhn.nauk; VOROB'YNA, L.V., kand.fiziko-
matematicheskikh nauk

Optical properties of milk. Trudy LFIKHP 13:28-34 '57.
(MIRA 13:6)

1. Kafedra obshchey i analiticheskoy khimii i kafedra fiziki
Leningradskogo tekhnologicheskogo instituta kholodil'noy
promyshlennosti.

(Milk---Spectra)

VOROB'YEVA, I.V.; PRUSSAKOVA, N.G.

Spectrum analysis of adrenocorticotrophic hormone (ACTH).
Trudy LFIKHP 15:87-91 '58. (MIRA 13:4)

1. Predstavlena Kafedroy fiziki Leningradskogo tekhnologicheskogo
instituta kholodil'noy promyshlennosti.
(Corticotropin--Spectra)

VOROB'YEVA, L. V.

PHASE I BOOK EXPLOITATION 307/1297

Vsesoyuznaya nauchno-tekhnicheskaya konferentsiya po prikladnoy radioaktivnoy i stabil'nykh izotopov i izucheniye v narodnom khozyaystve i nauke, Moscow, 1957

Polucheniye izotopov. Nauchnyye games-ustanovki. Radiometriya i dosimetriya; trudy konferentsii... (Isotope Production. High-energy Gamma-radiation Facilities. Radiometry and Dosimetry; Transactions of the All-Union Conference on the Use of Radioactive and Stable Isotopes and Radiation in the National Economy and Science) Moscow, Izd-vo AN SSSR, 1958. 293 p. 5,000 copies printed.

Sponsoring Agency: Akademiya nauk SSSR; Glavnoye upravleniye po ispol'zovaniyu atomnoy energii SSSR.

Editorial Board: Prolov, Yu.S. (Resp. Ed.), Zhavoronkov, N.M. (Deputy Resp. Ed.), Alikin, A.M., Alekseyev, B.A., Kochmarev, V.V., Lashchinsky, N.I., Mal'kov, T.F., Sinityn, V.I., and Popov, G.L. (Secretary); Tech. Ed.: Novichkov, N.D.

REMARKS: This collection is published for scientists, technologists, persons engaged in medicine or medical research, and others concerned with the production and/or use of radioactive and stable isotopes and radiation.

COVERAGE: Thirty-eight reports are included in this collection under three main subject divisions: 1) production of isotopes; 2) high-energy gamma-radiation facilities; and 3) radiometry and dosimetry.

TABLE OF CONTENTS:

PART I. PRODUCTION OF ISOTOPES

Prolov, Yu.S., V.V. Kochmarev, and Ye.Ye. Kulish. Development of Isotope Production in the Soviet Union. This report is a general survey of production methods, apparatus, raw materials, applications, investigations and future prospects for radio isotopes in the Soviet Union.

Card 2/12

Vorob'yeva, L.V., K.J. Kalugin, and Yu.M. Shtruktberg. Set-up for Measuring Individual Doses of Gamma-rays Within a Wide Range

226

Ismiderkhly, V.I. The Use of a Diffusion Chamber for Measuring Low Activity

235

Bol'shak, O.A., and A.M. Vyal'shin. Pocket Radiometers and Dosimeters

238

General description and electric circuit diagrams are given for a pocket-sized radiometer intended for ap-
proximate determination of gamma- and hard beta-ray
intensities above 0.1 Mr. Time lapses after onset of
radiation registration curves is determined for the
determination of intensity to 1000 Mr/h with an
accuracy of ± 20 percent. Working principle, components
and electric circuit diagram are given for a pocket-size
dosimeter capable of detecting approximate intensities
of gamma- and beta-radiation from 0.1 to 5000 μ r/sec and

Card 10/12

and above 0.3 Mr, respectively.

VOROB'YEVA, M.

30877. VOROB'YEVA, M., VYSKREBENTSEVA, E., AND KURSANOV, A.

M-Inozit v list'yakh chaya i puti yego obrazovaniya. Doklady Akad. nauk SSSR, Novaya seriya, T. LXVIII, No. 4, s. 734-40. -- Bibliogr: 8 nazv.

S/282/63/000/001/001/011
A059/A126

AUTHORS: Klinov, I.Ya., Vorob'yeva, M.A.

TITLE: The resistance to corrosion of some alloyed steels and titanium under the conditions of synthetic acetic acid production

PERIODICAL: Referativnyy zhurnal, ot del'nyy vypusk, 47. Khimicheskoye i kholodil'noye mashinostroyeniye, no. 1, 1963, 2, abstract 1.47. 4 (Vestn. tekhn. i ekon. inform. N.-1. in-t tekhn. ekon. issled. Gos. kom-ta Sov. Min. SSSR po khimii, no. 5, 1962, 41 - 44)

TEXT: The results are given of tests which have been performed under conditions resembling those found in operations on chrome, chrome-nickel, chrome-nickel-molybdenum, and chrome-molybdenum steels of the grades X25 T (Kh25T), X17 T (Kh17T), 1X18H9T (1Kh18N9T), OX21H5T (OKh21N5T), 1X18H12M2T (1Kh18N12M2T), 1X18H12M3T (1Kh18N12M3T), OX21H6M2T (OKh21N6M2T), X27H4M1T (Kh27N4M1T), X17M2T (Kh17M2T), X25M2T (Kh25M2T), and also on commercial titanium BT-1 (VT-1). Sheet steel, seamless tubes with untreated and turned surfaces, respectively, and also sheet steel samples having a welded

Card 1/2

3/282/63/000/001/001/011
A059/A126

The resistance to corrosion of some alloyed

joint were tested. The pipes were first heated to 700°C for 1 h and then cooled down in the air. Welding of the Kh17M2T steel was performed in argon atmosphere using a strip of the same steel as filler material. Commercial titanium VT-1 was also tested in the form of sheets, tubes and welded samples. From the test results it can be concluded that low-nickel steels, chrome-nickel steel OKh21N5T, and chrome-nickel-molybdenum steel OKh21N6M2T and Kh27N4M1T are corroded in solutions of acetic acids and a mixture of the oxidation products of n-butane to the same extent as the currently used steels 1Kh18N9T and Kh18N12M2T. Hence, under the conditions given, OKh21N5T grade-steel can be used instead of 1Kh18N9T, and OKh21N6M2T and Kh27N4M1T grade-steels instead of 1Kh18N12M2T. Chrome-molybdenum steel Kh17M2T is less resistant to the mixture mentioned containing more than 3% of formic acid at 140°C. Commercial-grade titanium VT-1 in a mixture of the oxidation products of n-butane containing up to 10% of formic acid at 140 and 160°C is not subjected to corrosion at all.

[Abstracter's note: Complete translation]

Card 2/2

VOROBYEVA, M.A.

PRIKHOT'KO, A.F.

24(7)

p.3

PHASE I BOOK EXPLOITATION 504/1365

L'vov. Universitet

Materialy I Vsesoyuznogo sveshcheniya po spektroskopii. t. 1: Molekulyarnaya spektroskopiya (papers of the 10th All-Union Conference on Spectroscopy. Vol. 1: Molecular Spectroscopy) [L'vov] Izd-vo L'vovskogo univ-ta, 1957. 499 p. 4,000 copies printed. (Series: Its: Fizichnyy sbirnyk, vyp. 3/8/)

Additional Sponsoring Agency: Akademiya nauk SSSR. Komissiya po spektroskopii. Ed.: Jager, S.L.; Tech. Ed.: Saranyuk, T.V.; Editorial Board: Lavstere, G.S., Academician (Resp. Ed., Deceased), Neporent, B.S., Doctor of Physical and Mathematical Sciences, Fabelinskiy, I.L., Doctor of Physical and Mathematical Sciences, Fabrikant, V.A., Doctor of Physical and Mathematical Sciences, Korotkiy, V.G., Candidate of Technical Sciences, Rayskiy, S.M., Candidate of Physical and Mathematical Sciences, Klimovskiy, L.K., Candidate of Physical and Mathematical Sciences, Miliyanchuk, V.S., Candidate of Physical and Mathematical Sciences, and Olsherman, A. Ye., Candidate of Physical and Mathematical Sciences.

Card 1/30

Sverdlov, L.M. Calculation and Interpretation of the Vibrational Spectra of Olefins	278
Sverdlov, L.M., and Ye. P. Kraynov. Vibrational Spectra and Potential Energy Constants of Cyclopropane and Deuterocyclopropane	282
Gorban', I.S., and A.A. Shishlovskiy. The Anomalous Dispersion of Light in Diluted Solutions	286
Lubchenko, A.Y. Light Dispersion in the Absorption Range of Impurity Centers	289
Yakovlev, G.M., D.S. Gorbenko-Germanov, N.A. Zankova et al. Study of Binary Americium Sulfates Using Absorption Spectra in Crystals	292
Vorobyeva, M.A. Birefringence of Some Organic Crystals With A Long-chain Molecular Structure	297

Card 19/30

VOROB'YEVA, M.A.; KLINOV, I.Ya.

Studying the corrosion of various alloys in fatty acids.

Trudy MIKHM 28:55-69 '64.

(MIRA 19:1)

YUNG, V.N.; VOROB'YEVA, M.A.

Conditions for stabilizing clinker compounds under temperatures
below sintering. Trudy MKHTI no.21:137-143 '56. (MIRA 9:9)
(Silicates)

V. R. BYEVA, M.A.

PHASE I BOOK SOV/3556

Moscow. Inzhenerno-fizicheskii Institut
Mekhanika i fizika eksperimental'nykh fiziki; (abstrukt) vyp. 2
(Some Problems in Experimental Physics); Collection of Articles.
Nr. 2) Moscow, Atomizdat, 1959. 123 p. 3,200 copies printed.

Sponsoring Agency: KSPR. Ministerstvo Vysshogo i Srednego
Special'nogo Obrazovaniya.

Ed.: B.M. Stepanov, Doctor of Physical and Mathematical Sciences.
Professor; Tech. Ed.: S.M. Popova.

PURPOSE: This collection of articles is intended for graduate
engineers and physicists engaged in the design of physics
(laboratory) apparatus, and automatic and telemechanic equipment.

CONTENTS: This collection of articles on experimental physics was
written by members of the Moscow Physics and Engineering Institute.

Each article is accompanied by drawings and references.
Belykh, B.A., B.L. Izhakov, and V.I. Izhakov. Operation of
Gas-Filled Counter During Over-Loading Pulses 32
The authors deal with the results of a study of the operation
of the MS-9, GS-9, and GS-30 standard counters under controlled
pulse feed operating conditions. The dependence of ionization
memory on pulse feed conditions was studied and a simple
method of measuring discharge propagation speed along the coun-
ter electrode is described.

Vlasov, A.D. Lenses Compensating the Effect of Intersection 40
Using in a Linear Proton Accelerator
The problem of compensating the unfavorable effect of inter-
section gaps on initial oscillations of particles in a linear
proton accelerator is discussed.

Izrael, I.Ye. Calculating the Profiles of Magnetic Poles 50
The article describes a method of computing profiles of the
poles of magnetic analyzers of charged particles for a given
field distribution in the plane of symmetry (the fringe effect
is not taken into account).

Malov, A.P. Some Ionic Optical Properties of Static Axially
Symmetrical Magnetic and Electric Fields 54
The author reports on the nonlinear study of the ionic optical
properties of crossed, exactly symmetrical, sectorial type elec-
tric and magnetic fields with unequal arm focusing and edges
of arbitrary form.

Vorobyeva, M.A. Sensitivity of the Glowing Dot Method 69
Kutylas-Uzyumov, V.O., P.A. Dolgobabin, A.M. Moskvichev, L.P.
Mokhov. Gating of a Plasma with a Pulse of About 100 nsec
in Copper and Iron 80

Dolobabin, P.A. and M.I. Iukhov. Polarization of Flow of A-mes-
ons at Sea Level 92

Polovnikov, V.I. Heat Transfer During Turbulent Mercury Flow
in Particular Channels 96
The author reports on experimental results on heat transfer of
mercury in turbulent channels for a range of Reynolds and
Prandtl numbers. The results are compared with theoretical
calculations and experimental data. A correlation equation is
proposed for the heat transfer coefficient. A preliminary analysis
of the results of the experiment is given.

Rebrikov, V.I. and V.I. Iukhov. Determination of the
Critical Point of a Plasma by the Method of the Glowing Dot 100
Vlasov, B.M. and V.I. Iukhov. The Theory of a Radio Spoke
117
The author reports on the results of the study of the properties of
a radio spoke in the electron beam of a linear accelerator.

S/081/61/000/022/074/076
B144/B138

AUTHORS: Klinov, I. Ya., Vorob'yeva, M. A.

TITLE: Chemical resistance of some coating materials and their use
in protecting chemical apparatus from corrosion

PERIODICAL: Referativnyy zhurnal. Khimiya, no. 22, 1961, 483, abstract
22P283 (Tr. Mosk. In-ta khim. mashinostr., v. 22, 1960,
159 - 168)

TEXT: The chemical resistance to the direct effect of aggressive media
was studied in the following compounds: ПСР (PSG), ПС-2 (PS-2), and
ПТ (PT) type polyisobutylene (I), a combination of I and ПОВ-30 (POV-30)
and ПОВ-50 (POV-50) type polyethylene, "Brisol", "Relin", and 829-, 1976-,
and 2566-type rubbers. Corrosion resistance was estimated from the degree
of swelling and the variations in the physical and mechanical properties
of the coating. Relin is not suitable as an anticorrosive material,
Brisol is stable in weakly acid and low-alkaline media at 60°C, its chemi-
cal resistance is higher than that of ruberoid. 829-, 1976-, and 2566-
-type rubbers are stable in up to 50% H₂SO₄ at 60 - 90°C and unstable
Card 1/2 ✓

Chemical resistance of some ...

S/081/61/000/022/074/076
B144/B138 ✓

in 20% HCl and HNO_3 . HNO_3 causes the destruction of the material, which explains the reduction in the mechanical stability of PSG and POV-30. I PS-2 shows the highest HNO_3 resistance. Coatings on PSG, PS-2, POV-30, and POV-50 basis are resistant to HCl and to H_2SO_4 up to 75% at 60°C. POV-30 and POV-50 can withstand the effect of 92% H_2SO_4 up to six months. Data are given on the chemical stability of bonded and welded seams with regard to different aggressive media, when adhesives nos. 8 and 88, I solution and carbinol glue are used. [Abstracter's note: Complete translation.]

Card 2/2

S/051/62/012/006/012/020
E039/E420

243000

AUTHOR: Vorob'yeva, M.A.

TITLE: The sensitivity of the radiant point method. III

PERIODICAL: Optika i spektroskopiya, v.12, no.6, 1962, 765-768

TEXT: The effect of the appearance of a transition region between two regions of refractive index μ_1 and μ_2 on the sensitivity of the radiant point method is examined more rigorously than in an earlier work. The reduction in intensity is shown by the values of light intensity J given by

$$J_{\max} = 1 + 2\pi n \Delta$$

and

$$J_{\min} = 1 - 2\pi n \Delta$$

The parameter Δ is plotted as a function of ξ for values of $\beta = 0, 0.7$ and 1.0

$$\xi = x \sqrt{2/z\lambda} \quad \text{and} \quad \beta = b \sqrt{2/z\lambda}$$

When $\beta = 0.7$ the maximum value of Δ is at $\xi = 0.65$ and is Card 1/2.

S/051/62/012/006/012/020
E039/E420

The sensitivity of the radiant ...

very near to the corresponding value at $\beta = 0$. When $\beta = 1$ the maximum occurs at near $\beta = 1$. The values of Δ attain the experimental values at $\beta = 0.7$ and are plotted as a function of β for this condition. $\Delta = 0.5$ at $\beta = 0$ and 0.25 at $\beta = 0.7$. A value for the visibility V is also calculated as a function of Δ .

$$V = \frac{J_{\max} - J_{\min}}{J_{\max} + J_{\min}} = 6.3n$$

Values of n are given for which the nonuniformity ceases to be obvious, typically $n = 0.0144$ at $\beta = 0.7$. Values of β up to 0.3 Fresnel zones have no influence on the sensitivity of the method. There are 3 figures and 2 tables.

SUBMITTED: May 4, 1961

Card 2/2

S/081/61/000/010/007/029
B117/B207

AUTHORS: Klinov, I. Ya., Vorob'yeva, M. A., Borisova, A. S.

TITLE: Study of the corrosion resistance of aluminum in sulfuric acid and mixture

PERIODICAL: Referativnyy zhurnal. Khimiya, no. 10, 1961, 285, abstract 104193 (10I193). ("Tr. Mosk. in-ta khim. mashinostr.", v. 22, 1960, 96-104)

TEXT: The corrosion rate of aluminum of all types was found to increase with the H_2SO_4 concentration, and to reach its maximum in 80% H_2SO_4 (up to 1.2 - 1.3 g/m² hr). It is pointed out that rolled aluminum tends to regular corrosion, whereas cast aluminum tends to intercrystalline cracking. The corrosion rate of all types of aluminum increases considerably at a temperature rise from 20° to 80°C, in any H_2SO_4 concentration. Rolled aluminum of the AB-000 (AV-000) and A-00 (A-00) types, as well as

Card 1/2

Study of the corrosion resistance...

S/081/61/000/010/007/029
B117/B207

A-1 (A-1), may be used in low-concentrated H_2SO_4 at $20^{\circ}-25^{\circ}C$. [Abstracter's
note: Complete translation.]

Card 2/2

VOROB'YEVA, M.A.

Sensitivity of the radiant point method. Part 3. Opt. 1 spektr.
12 no.6:765-768 Je '62. (MIRA 15:5)
(Diffraction)

KLINOV, I.Ya.; VOROB'YEVA, M.A.

Chemical stability of certain lining materials and their use for
the protection of chemical apparatuses from corrosion. Trudy
MIKHM 22:159-168 '60. (MIRA 14:1)

(Resins, Synthetic)
(Corrosion-resistant materials)

VOROB'YEVA, M. A.

507/552

PLATE 1 BOOK EXPLANATIONS

Результаты химического обследования (автор Д. И. Мандельберг).
Силы: сборник статей по химии и технологии силикатов, вып. 1 (Силикаты).
Сборник статей по химии и технологии силикатов, вып. 1 (Силикаты, No. 1).
Москва, Стройиздат, 1979. 103 с. Серия альбомов. 3,000 копий
печатаются.

Редакционный Совет: М. А. Матвеев (зам. ред.), Т. А. Бутт, и М. О. Рубинский.
Изд. издательского дома: Т. А. Мандельберг. Изд. 1.1. Москва.

ПРЕДМЕТЬ: This booklet is intended for chemists and geologists interested in
silicate analysis.

СОДЕРЖАНИЕ: This is a collection of articles on the chemistry and technology of silicates.
The contributing authors discuss the effect of admixtures on silicate
processes and on the properties of Portland cements. The text also discusses
the properties of certain glasses, the processing of ceramic materials, the
process of drying facing tiles, the stability of solid solutions of calcium
silicates, the activation of cement, the production of aluminum cement,
the preparation of pulping rolls, the interaction of quartz with lime, and
various problems related to the production of silica-calcite materials.
No personalities are mentioned. References are given at the end of each
article.

TABLE OF CONTENTS

Sil'vestrovich, S. I. The Properties of Fluoride and Phosphate Opaline Glasses.	3
Rubinskaia, I. I., and T. A. Gurevich. The Effect of Small Additions of Certain Oxides on the Process of Sintering Alumina.	14
Mamontova, N. A., and A. A. Mayer. Petrographic Investigation of Processes Occurring During Annealing and Cooling of Ceramic Materials.	20
Grushko, G. A. Intensifying the Process of Drying Facing Tiles During Radi- ation Heat Exchange.	32
Butt, T. A., and T. V. Timshel. Stability of Solid Solutions of Calcium Alumoferrites With Increased Temperature.	46
Vorob'yeva, M. A., and M. A. Vorob'yeva. The Effect of Certain Admixtures on the Physical and Chemical Properties of Magnesia-rich Portland Cement.	52
Gil'denberg, Z. G., and S. I. Penderashvaya. Activating Cement by Grinding in Vibrating Mills.	59
Rumyantsev, A. M., and Ye. S. Kovalev. On the Production of Aluminous Cement by Sintering in Rotary Mills.	70
Matveyev, M. A., and A. I. Babitskiy. New Method for the Preparation of Pulping Rolls.	76
Matveyev, M. A., and G. V. Gerasimchenko. Increasing the Strength of Quartz- Cement Pulping Rolls.	82
Butt, T. A., and A. A. Mayer. Quartz-Lime Interaction at Temperatures Below 120°.	88
Satalkina, A. V., and O. V. Rumyantsev. Some Problems in the Production of Silicate-Calcite Materials.	100
AVAILABLE: Library of Congress Card 3/3	507/552 5-18-60

VOROB'YEVA, M.A.

Birefringence of crystals of the aliphatic series. Nek. vop.
eksp. fiz. no.1:76-86 '59. (MIRA 13:2)
(Refraction, Double)
(Aliphatic compounds--Optical properties)

VOROB'YEVA, M.A.

Sensitivity of the luminous point method. Nek.vop.eksp.fiz.
no,2:69-79 '59. (MIRA 13:2)
(Refraction) (Diffraction)

VOROB'YEVA, M. A.

USSR/Chemical Technology - Chemical Products and Their Application. Silicates.
Glass. Ceramics. Binders, I-9

Abst Journal: Referat Zhur - Khimiya, No 19, 1956, 62363

Author: Yung, V. N., Vorob'yeva, M. A.

Institution: None

Title: Conditions of Stable Existence of Clinker Compounds at Temperatures
Below Sintering

Original
Periodical: Tr. Mosk. khim. tekhnol. in-ta, 1956, No 21, 137-143

Abstract: A study was made of the behavior of clinker minerals and of industrial clinkers at temperatures below sintering. All the specimens were held for a definite length of time at 600, 700, 800, 900, 1,000, 1,100, 1,200°. It was found that tricalcium silicate as such is not stable at a temperature below sintering and maintained within the limits of 800-1,200° it splits off free Ca oxide. At these temperatures free lime is also liberated from Ca aluminoferrites and tricalcium aluminate which are present in the clinker. In a reducing

Card 1/2

USSR/Chemical Technology - Chemical Products and Their Application. Silicates.
Glass. Ceramics. Binders, I-9

Abst Journal: Referat Zhur - Khimiya, No 19, 1956, 62363

Abstract: medium iron-containing minerals of the clinker undergo decomposition to a greater extent. Investigations of the properties of clinkers which had been subjected to the above-described thermal treatment, have shown that free lime liberated in the course thereof has no detrimental effect on uniform change in volume and strength of the cement, in contrast with the free lime which has not been taken up in the sintering zone.

Card 2/2

VOROB'YEV, Kh.S.; VOROB'YEVA, M.A.

Effect of various admixtures on physical and mechanical properties
of magnesian portland cements. Silikaty no.1:52-58 '59.

(MIRA 13:2)

(Portland cement)

VOROB'YEVA, M. A.

VOROB'YEVA, M. A. --"Conditions for the Stable Existence of Cinder Compounds at Temperatures below Sintering Temperatures." Min Higher Education USSR. Moscow Order of Lenin Chemicotechnological Inst imeni D. I. Mendeleev. Moscow, 1955. (Dissertation for the Degree of Candidate in Technical Science).

SO Knizhanay letopis'
No 2, 1956

KLINOV, I.Ya.; VOROB'YEVA, M.A.; BORISOVA, A.S.

Investigating the corrosion resistance of aluminum in sulfuric acid
and "melange." Trudy MIKHM 22:96-104 '60. (MIRA 14:1)
(Aluminum-Corrosion) (Sulfuric acid)

KLINOV, I.Ya., doktor tekhn.nauk; VOROB'YEVA, M.A.

Behavior of some plastic materials under conditions of the
production of synthetic acetic acid by n-butane oxidation.
Khim.prom. no.10:769-772 0 '62. (MIRA 15:12)

(Plastics—Testing)
(Acetic acid) (Butane)

VOROB'YEVA, M.A.; KLINOV, I.Ya.

Effect of various factors on the corrosion rate of stainless steels
in acetic acid solutions. Izv.vys.ucheb.zav.; khim. i khim.tekh. 7
no.2:327-334 '64. (MIRA 18:4)

1. Moskovskiy institut khimicheskogo mashinostroyeniya, kafedra
korrozii khimicheskoy apparatury.

ACCESSION NR: AP4041686

S/0153/64/007/002/0327/0334

TITLE: Effect of different factors on the corrosion rate of stainless steels in acetic acid solutions.

AUTHOR: Vorob'yeva, M. A., Klinov, I. Ya.

SOURCE: IVUZ. Khimiya i khimicheskaya tekhnologiya, v. 7, no. 2, 1964, 327-334

TOPIC TAGS: stainless steel, corrosion, acetic acid corrosion, aeration, acetic formic acid corrosion, electrochemical behavior, activation passivation, chromium nickel steel, chromium nickel molybdenum steel, anodic polarization, cathodic polarization, corrosion resistance

ABSTRACT: The effects were studied of aerating and of admixing up to 10% formic acid on the rate of corrosion and the electrochemical behavior of Cr-Ni and Cr-Ni-Mo steels (1Kh18N9T, 1KhN12M2T, OKh21N5T and OKh21N6M2T) in 60, 80 and 90% acetic acids at 18, 60 and 90C. The anodic and cathodic polarization and the rate of corrosion in Cr-Ni steels in 60 and 90% acetic acid at 18 and 60C was affected

Card 1/3

ACCESSION NR: AP4041686

little by the admixture of up to 5% formic acid; the rate of corrosion of the Cr-Ni steels was insignificant under these conditions. At 90C the admixture of formic acid retarded the anodic polarization of the investigated steels in 60 and 90% acetic acid with the anodic polarization of the Cr-Ni steels being hampered more by an increase in formic acid content than the anodic polarization of the Cr-Ni-Mo steels. The Cr-Ni and Cr-Ni-Mo steels were polarized more readily and their rate of corrosion was less upon application of anodic current in aerated acetic acid solutions containing formic acid than in unaerated solutions of the same concentration. All the steels investigated were converted to the active state in unaerated acetic acid solutions containing admixtures of formic acid after treatment with cathodic current; the Cr-Ni-Mo steels were activated in solutions containing higher formic acid content. The Cr-Ni steels 1Kh18N9T and OKh21N5T do not withstand the action of 60 and 90% acetic acids with formic acid at 90C or boiling temperature. The corrosion resistance of the Cr-Ni-Mo steels is not sufficient at 90C in unaerated 60 and 90% acetic acid solutions containing 3% formic acid. Orig. art. has: 3 figures and 2 tables

Card 2/3

ACCESSION NR: APL041686

ASSOCIATION: Kafedra korrozii khimicheskoy apparatury, Moskovskiy institut
khimicheskogo mashinostroyeniya (Department of Corrosion of Chemical Apparatus,
Moscow Institute of Chemical Machinery Construction)

SUBMITTED: 10May63

ENCL: 00

OTHER: 004

SUB CODE: MM, CC

NR REF SOV: 003

Card 3/3

VOROB'YEVA, M.D., tekhnik; DUSHIN, B.M., inzh.; FASTOVETS, O.S., inzh.

New developments in the processing of split leather. Kozh.-obuv.
prom. 2 no. 12:32-33 D '60. (MIRA 14:1)
(Leather)

- Vorob'yeva, M.I.

VOROB'YEVA, M.I., kandidat tekhnicheskikh nauk, redaktor; POPOVA, S.M.
~~tekhnicheskiiy redaktor~~

[Modern technology of precision casting using fusible patterns;
proceedings of a session] Sovremennaya tekhnologiya tochnogo
lit'ia po vyplavlennym modeliam; trudy sessii. Pod red.
M.I. Vorob'yeva, Moskva, Gos. nauchno-tekhn. izd-vo mashinostroit.
lit-ry. 1954. 106 p. (MLRA 8:8)

1. Vsesoiuznoye nauchnoye inzhenerno-tekhnicheskoye obshchestvo
liteyshchikov, Moscow.
(Founding)

VOROB'YEV, M.
CA

112

meso-Inositol in tea leaves and its formation paths.
A. L. Kursanov, M. Vorob'eva, and E. Vyskrebentseva.
Doklady Akad. Nauk S.S.S.R. 68, 737-40(1949); cf.
C.I. 44, 11724. -- All inositol in tea leaves (Georgian-
unrated species) is shown to be *meso*-inositol by chem.
analysis (Smirnov, C.I. 30, 4524) and by biol. method
in cultivation of *Saccharomyces carlsbergensis*, capable of
utilizing only the *meso* form. Infiltration into the leaves
of solns. of glucose, fructose, sucrose, and glucose 1-phos-
phate leads only to *meso*-inositol formation, part of which
is in free state, but the bulk forms some other compds.
from which *meso*-inositol can be obtained by 12-hr. hy-
drolysis with 22% H₂SO₄. The synthesis from sucrose is
3 times faster than that from glucose, probably caused
by the presence of the glucoside link; results with glucose
1-phosphate are similar to those with sucrose. Maltose
is not utilized, nor is rhamnose, glyceraldehyde, and
glycolaldehyde, as well as glycerol and pyruvic acid.

G. M. Kosolapoff

VOROB'YEVA, M. M.

Dissertation: "The Significance of Adenosinetriphosphoric Acid in the Reproduction of the Influenza Virus." Cand Biol Sci, Acad Med Sci USSR, 17 Jun 54. (Vechernyaya Moskva, Moscow, 8 Jun 54)

80: SUM 318, 23 Dec 1954

VOROBIEVA, M. M.

USSR/Medicine - Virology

Card 1/1 :

Authors : Tsvartnitskiy, G. I., and Vorobieva, M. M.

Title : Effect of adenosinetriphosphoric acid on the multiplication of influenza virus

Periodical : Dokl. Ak. Nauk SSSR, 216: 718, August 11, 1954

Abstract : Microbiological data on the effect of adenosinetriphosphoric acid (ATP) on the multiplication of influenza viruses. Fifteen references; 12 in Russian, 3 in English.

Institution : Acad. of Med. Sci. USSR, The N. I. Ivanovskiy Institute of Virology

Presented by : Academician V. A. Engelhardt, April 21, 1954

VOROB'YEVA, M. M.

20-2-52/62

AUTHOR
TITLE

VOROB'YEVA, M.M.

The Proteins of Bacterium Paracoli, as Affected by Phage
(Vliyaniye faga na belki Bakterium paracoli. Russian)
Doklady Akademii Nauk SSSR, 1957, Vol 115, Nr 2, pp 385-388 (U.S.S.R.)

PERIODICAL
ABSTRACT

In the present work the electrophoresis method was used for the investigation of the protein of the B. paracoli during the latent period of development of the phage. From 2 illustrations it may be seen that the greatest changes occur in the protein fractions I and II which move in the electric field. A strong reduction to complete disappearance of the protein was observed. Also the proteins (fraction IV) moving quickest decreased. Thus we state the disturbance of several protein fractions in the case of an infection of the phage by means of bacteriae. It does not seem impossible that their decomposition products are used for the formation of the virus particles. No new protein fraction could be discovered in connection with the increase of phage. The electric photo-diagrams of the B. paracoli - proteins bred on meat-broth on glucose, were greatly different from those grown without glucose; this went so far that they could be taken for proteins of other kinds of bacteriae. Also here several protein fractions decreased, but less intensively inspite of the more intensive development of phage in consequence of the addition of glucose. Also the development of the bacteriae themselves is accelerated by glucose.

Card 1/2

20-2-52/62

The Protein of Bacterium Paracoli, as Affected by Phage

With this addition the bacteria are less liable to be destroyed by phage. Glucose increases the intensity of the synthesis processes so that the requirements of the phage can apparently be satisfied by the absorption of nutritive substances from the external sphere. These differences can, however, also have been caused together with the changes of protein secretion by bacteria into the nutritive soil. (3 illustrations and 2 Slavic references).

ASSOCIATION

Institute for Virusology Im.D.I.Ivanovskiy of the Academy of Medical Sciences of the U.S.S.R.
(Institut virusologii im. D.I. Ivanovskogo Akademii meditsinskikh nauk SSSR)

PRESENTED BY
SUBMITTED
AVAILABLE

ENOELOGARIN, V.A., Member of the Academy, April 10, 1957
8.4.1957
Library of Congress

Card 2/2

VOROB'YEVA, M.M.

Adenosinetriphosphatase in *B. paracoli* during the latent period of phage development. Vop' virus. 4 no.1:100-103 Ja-F '59. (MIRA 12:4)

1. Laboratoriya biokhimii Instituta virusologii imeni D.I. Ivanovskogo AMN SSSR, Moskva.

(PARACOLOBACTRUM, metabolism,

ATPase in various stages of phage develop. (Rus))

(BACTERIOPHAGE,

of Paracolobactrum, ATPase activity during various stages of develop. (Rus))

(ADENYLYROPHOSPHATASE,

in Paracolobactrum, in various stages of phage develop. (Rus))

VOROB'YEVA, M.M.

Effect of the culture medium on proteins in paracolon bacilli. Vop.
med.khim. 5 no.4:251-253 JI-Ag '59. (MIRA 12:12)

1. Laboratoriya biokhimii Instituta virusologii imeni D.I. Ivanovsko-
go AMN SSSR, Moskva.
(PARACOLOBACTERUM metab.)
(PROTEINS metab.)

VOROB'YEVA, M.S.

Experimental study of humoral immunity in reptiles infected by
tick-borne encephalitis virus. Vop. virus. 10 no.1:36-41 Ja-F
'65. (MIRA 18:5)

1. Institut poliomyelita i virusnykh entsefalitov AMN SSSR,
Moskva.

VOROB'YEVA, M.S.; LEVKOVICH, Ye.N.

Sensitivity of cold-blooded animals to the virus of tick-borne encephalitis. Zool. zhur. 43 no.7:1084-1087 '64.

(MIRA 17:12)

1. Institute of Polyomyelitis and Viral Encephalites, Academy of Medical Sciences of the U.S.S.R., Moscow.

VOROB'YEVA, M.T., kand. tekhn. nauk

Use of metrology and mathematical statistics in the quality
control of woodpulp production. Bum. prom. no.3:3-7 Mr '64.
(MIRA 17:3)

1. Moskovskiy filial Vsesoyuznogo nauchno-issledovatel'skogo
instituta tsellyulozno-bumazhnoy promyshlennosti.

SNESAREV, K.A.; VOROB'YEVA, M.T.; AGEYEV, M.Ye.

Rapid method for determining the temperature of colophony
softening. Gidroliz. i lesokhim. prom. 9 no.4:17-18 '56.
(MLRA 9:11)

1. TSentral'nyy nauchno-issledovatel'skiy lesokhimicheskiy
institut.

(Gums and resins)

SNESAREV, Kirill Andreyevich; ZARAKOVSKAYA, Anna Iosifovna; VOROB'YEVA,
Mariya Trofimovna; SUMAROKOV, V.P., red.; IOFINOVA, TS.B., red.
izd-va; PARAKHINA, N.L., tekhn.red.

[Metrological principles of the analytical control of chemical
industries] Metrologicheskie osnovy analiticheskogo kontrolya
khimicheskikh proizvodstv. Moskva, Goslesbumizdat, 1960. 205 p.
(MIRA 13:9)

1. TSentral'nyy nauchno-issledovatel'skiy lesokhimicheskiy insti-
tut (for Sumarokov).

(Chemistry, Analytic--Quantitative)

VOROB'YEVA, M.T.

USSR/Chemical Technology - Chemical Products and Their
Application. Wood Chemistry Products. Hydrolysis Industry I-9

Abs Jour : Ref Zhur - Khimiya, No 1, 1958, 2666

Author : Snasarev, K.A., Vorob'yeva, M.T.

Inst : -

Title : Evaluation of the Color of Turpentine.

Orig Pub : Gidroliznaya i lesokhim. prom-st', 1957, No 5, 17-18

Abstract : To measure the intensity of turpentine coloration a method of equalizing is proposed. The mean quadratic error of this method is of ± 1.7 mm, or $\pm 4\%$. The adopted norm of turpentine coloration is equal to that of a column of a type solution (solution of potassium bichromate of a concentration of 0.0125 g/liter) measuring 90 mm.

Card 1/1

POKROVSKAYA, N.V.; VOROB'YEVA, M.T.

Development of the methods for obtaining glucose oxidase preparations.
Trudy TSentr.nauch.-issl.inst.piv.,bezalk. i vin.prom. no.9:69-78
'62. (MIRA 16:10)

VOROB'YEVA, M.T.

SNESAREV, K.A.; VOROB'YEVA, M.T.

Evaluation of turpentine color. Hidroliz. i lesokhim.prom. 10
no.5:17-18 '57. (MIRA 10:8).

1.Tsentral'nyy nauchno-issledovatel'skiy lesokhimicheskiy institut.
(Turpentine--Standards)

VOROB'YEVA, M.T.
SNESAREV, K.A.; VOROB'YEVA, M.T.

Apparatus for determining the softening temperature of wood
pitch and abietic tar. *Gidroliz. i lesokhim. prom.* 9 no.8:
17 '56. (MLRA 10:2)

1. Tsentral'nyy nauchno-issledovatel'skiy lesokhimicheskiy institut.
(Chemical apparatus) (Pitch) (Tar)

SNESAREV, K.A.; VOROB'YEVA, M.T.; ZARAKOVSKAYA, A.I.

Rapid method for determining moisture in gum. Gidrolis.
i lesokhim. prom. 9 no.4:19 '56. (MLRA 9:11)

1. TSentral'nyy nauchno-issledovatel'skiy lesokhimicheskiy
institut.

(Gums and resins)

SNESAREV, K.A., doktor khimicheskikh nauk; VOROB'YEVA, M.T., nauchnyy sotrudnik.

Speedy method for determining the temperature of rosin softening without using mercury. Der.1 lesokhim.prom. 2 no.9:15-17 S '53. (MLRA 6:8)

1. TsNILKhI.

(Gums and resins)

SHESAREV, K.A.; VOROB'YEVA, M.T.

~~SECRET~~
Present state and objectives for the improvement of the quality control
of rosin. Sbor.trud. TSHILKHI no.12:151-166 '57. (MIRA 13:10)
(Gums and resins--Quality control)

SNESAREV, K. A. ; YOROB'YEVA, M. T.

Method and standards for the selection of rosin samples. Sbor.trud.
TSNIIKHI no.13:129-140 '59. (MIRA 13:10)
(Gums and resins)

VOROB'YEVA, N.A.; KAGAN, Yu.M.; MILNIN, V.M.

Electron velocity distribution in a positive column in a
gaseous mixture. Zhur. tekhn. fiz. 34 no.5:828-832 May'64
(MIRA 17:8)

1. Leningradskiy gosudarstvennyy universitet imeni Zhdanova.

L 9921-63

ACCESSION NR: AP3000013

cylindrical and spherical probes were used. The measurements were carried out at pressures from 10^{-4} to 10^{-1} mm Hg, and for discharge current values from 1.0 to 1.0 amperes. The quantities measured were the probe current and its second derivative for different values of the potential between the probe and the plasma. The apparatus used for the measurements is described in the

Address: Leningradskiy gosudarstvennyy universitet Im. A. A. Zhdanova
(Leningrad State University)

SUBMITTED: 06 Apr 62 DATE ACQ: 12 Jun 63

ENCL: 00

SUB CODE: PH

NR REF SOV: 004

OTHER: 004

1m/ja
Card 2/2

VOROB'YEVA, N.A.; KAGAN, Yu.M.; MILENIN, V.M.

Electron distribution function in a positive discharge column in neon and helium. Zhur.tekh.fiz. 34 no.11:2079-2081 N '64.

(MIRA 18:1)

1. Leningradskiy ordena Lenina gosudarstvennyy universitet imeni A.A.Zhdanova.

VOROB'YEVA, N. A.; KAGAN, Yu. M.; LYAGUSHCHENKO, R. I.; MILENIN, V. M.

3

"The Energy Distribution of Electrons in the Discharge of the Positive Column."
report submitted to 11th Intl Spectroscopy Colloq, Belgrade, 30 Sep-4 Oct 63.